



Multi-Purpose Penetrating Sealer

Aquaseal **DO-IT-ALL** is a multi-purpose penetrating clear sealer for use over any deteriorated surface requiring restoration or as a protective coating on new surfaces. Containing pure hybrid 100% acrylic, **DO-IT-ALL** is shipped in a concentrated form and is diluted prior to use with conventional tap water. A diluted 3.79L container of **DO-IT-ALL** will cover approximately 24-27 square metres (275-300 sq.ft.). The product also contains a high amount of mildicide and will help prevent the growth of mold and fungus on interior and exterior surfaces.

DO-IT-ALL can be used on:

- Drywall
- Paint
- Wood
- Metal
- Cement Blocks
- Concrete
- Brick
- Plaster
- Stucco
- Concrete Pavers
- Asphalt shingles
- Clay roof tiles
- Concrete roof tiles
- Leaking roofs
- Painted walls

DO-IT-ALL will dry in approximately 30 minutes to 1 hour under normal conditions and may be re-coated after 2 hours.

Application:

DO-IT-ALL is supplied in a 3.79L concentrate and **must be diluted** with 11.4L of tap water (for most applications) prior to use and thoroughly mixed. The surface over which the sealer is to be applied should be cleaned to remove as much deteriorated residue, flakes, or powder as possible. The diluted product is best rolled or sprayed onto the surface, but can be brushed as well. Spraying can be by airless or garden type pump-up sprayer. Apply the diluted product evenly over the surface to thoroughly wet the area. Ideal application temperature is above 10C to facilitate drying time. It is recommended that for best results, two coats be applied.

Coverage:

3.79L of diluted **DO-IT-ALL** will cover approximately 24-27m² – so a 3.79L container of concentrate, diluted 3:1 with water, makes 15.2 litres which is enough product to cover up to 108 square metres. Coverage will vary due to the profile and porosity of the surface.

Clean-Up:

All tools can be cleaned with a solution of soap and water. **DO-IT-ALL** is extremely fast drying so caution should be taken to have a wet rag available to remove any overspray of the product

Caution:

Protect the product from freezing. Do not take internally and avoid contact with eyes and skin by wearing protective clothing and goggles. **KEEP OUT OF REACH OF CHILDREN.**

Liability Limitations:

DO-IT-ALL is designed to perform as stated. However, Aquaseal cannot control application conditions or any misuse of the product. It is up to the user to test the product on a small area to determine the suitability of this product for their application. Should any problems occur with the use of this product, Aquaseal accepts no liability beyond replacement of the product or a refund equal to the purchase price.

Dilution Rates:

Dilute with tap water at the following ratios prior to use:

SURFACE	USES	DILUTION
Drywall	<ol style="list-style-type: none"> 1. As a mildew and mold prevention prior to painting 2. Apply to wall prior to installing drywall to prevent mold and mildew from forming in the wall cavity behind the drywall 	3 to 1
Paint	<ol style="list-style-type: none"> 1. Apply to peeling paint – just scrape off any loose or blistered areas, apply DO-IT-ALL and then re-paint 2. As a base coat prior to painting, preventing mold and mildew from forming 3. As a top coat on exterior finishes to prevent unsightly moss and fungus growth 	3 to 1
Wood	<ol style="list-style-type: none"> 1. As a sealer and preservative on decks, windows, doors, etc. 2. Restores dried out wood with a 'new look' 	3 to 1
Metal	<ol style="list-style-type: none"> 1. As a base coat or primer 2. Over old paint before re-painting 	3 to 1
Cement Blocks	<ol style="list-style-type: none"> 1. As a base coat prior to painting – reduces the amount of paint required by up to 30% 2. As a clear waterproof sealer 	3 to 1
Concrete	<ol style="list-style-type: none"> 1. As a penetrating sealer on concrete floors in warehouses, workshops, etc. to prevent dust 2. Seal driveways to enhance the appearance and protect against staining 	3 to 1
Concrete Pavers	<ol style="list-style-type: none"> 1. Seals new and existing pavers to prevent damage from UV rays, freeze/thaw, etc. 2. Rejuvenates old pavers and restores the original look 	2 to 1 3 to 1
Brick	<ol style="list-style-type: none"> 1. Forms a barrier to prevent the brick from soaking up moisture and causing flaking and damage from freeze/thaw. 	3 to 1
Plaster	<ol style="list-style-type: none"> 1. As a sealer prior to painting – reduces the amount of paint required by up to 30% 2. Prevents the growth and spread of mildew and mold 	3 to 1
Stucco	<ol style="list-style-type: none"> 1. Use on powdery old stucco to stop further deterioration 2. Seals and rejuvenates old stucco 3. Gives a clear waterproof coating to existing stucco 4. Apply prior to painting to reduce the amount of paint required 5. When applied as a clear top coat, will prevent the forming of mildew, moss and black fungus 	2 to 1 3 to 1
Asphalt Shingles	<ol style="list-style-type: none"> 1. When applied as a clear top coat, will prevent the forming of mildew, moss and black fungus 2. Rejuvenates old shingles and extends the life by up to 30% 3. Seals the granules to the single and prevents curling and lifting¹ 	3 to 1
Clay or Concrete Roof Tiles	<ol style="list-style-type: none"> 1. Rejuvenates old tiles and restores them to close to their original color 2. Seals the tiles and replaces the original glaze to waterproof and protect from UV rays 3. When applied as a clear top coat, prevents the formation of mildew, moss and black fungus 	3 to 1
Roof Leaks	<ol style="list-style-type: none"> 1. Will seek out and seal small roof leaks 	2 to 1

Note: 2:1 dilution = 7.5L of water to 3.79L of DO-IT-ALL concentrate
 3:1 dilution = 11.4L of water to 3.79L of DO-IT-ALL concentrate